

# Product data sheet

Specifications



## Thermal overload relay, TeSys Deca, 2.5-4A, 1NO+1NC, class 20, lugs ring terminal

LRD08L6

### Main

|                                     |   |
|-------------------------------------|---|
| Range                               | TeSys<br>TeSys Deca   |
| Product Name                        | TeSys LRD<br>TeSys Deca   |
| Product Or Component Type           | Differential thermal overload relay   |
| Device Short Name                   | LRD   |
| Relay Application                   | Motor protection  |
| Product Compatibility               | LC1D09<br>LC1D38<br>LC1D32<br>LC1D12<br>LC1D18<br>LC1D25  |
| Network Type                        | DC<br>AC  |
| Thermal Overload Class              | Class 20 conforming to IEC 60947-4-1  |
| Thermal Protection Adjustment Range | 2.5...4 A   |
| [Ui] Rated Insulation Voltage       | Power circuit: 600 V conforming to CSA<br>Power circuit: 600 V conforming to UL<br>Power circuit: 690 V conforming to IEC 60947-4-1 |

### Complementary

|   |   |
|---|---|
| Network Frequency                           | 0...400 Hz  |
| Mounting Support                            | Plate, with specific accessories<br>Rail, with specific accessories<br>Under contactor    |
| Tripping Threshold                          | 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1  |
| Auxiliary Contact Composition               | 1 NO + 1 NC   |
| [Ith] Conventional Free Air Thermal Current | 5 A for signalling circuit  |
| Permissible Current                         | 3 A at 120 V AC-15 for signalling circuit<br>0.22 A at 125 V DC-13 for signalling circuit |
| [Ue] Rated Operational Voltage              | 690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1                         |
| Associated Fuse Rating                      | 4 A gG for signalling circuit<br>4 A BS for signalling circuit                            |
| [Uimp] Rated Impulse Withstand Voltage      | 6 kV  |
| Phase Failure Sensitivity                   | Tripping current 130 % of Ir on two phase, the last one at 0                              |
| Control Type                                | Red push-button: stop<br>Blue push-button: reset  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                          |  |
|--------------------------|--|
| Temperature Compensation | -20...60 °C  |
| Connections - Terminals  | Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² flexible without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² flexible with cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² solid without cable end<br>Power circuit: lugs-ring terminals |
| Tightening Torque        | Control circuit: 1.7 N.m - on screw clamp terminals<br>Power circuit: 2.3 N.m - on lugs-ring terminals M4  |
| Height                   | 66 mm  |
| Width                    | 45 mm  |
| Depth                    | 76 mm  |
| Net Weight               | 0.144 kg   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Climatic Withstand                    | conforming to IACS E10   |
| Ip Degree Of Protection               | IP20 conforming to IEC 60529   |
| Ambient Air Temperature For Operation | -20...60 °C without derating conforming to IEC 60947-4-1   |
| Ambient Air Temperature For Storage   | -60...70 °C  |
| Mechanical Robustness                 | Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7<br>Vibrations: 3 GN conforming to IEC 60068-2-6                                  |
| Dielectric Strength                   | 1.89 kV at 50 Hz conforming to IEC 60947-1   |
| Standards                             | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-4-1<br>CSA C22.2 No 60947-5-1<br>EN 50495 |
| Product Certifications                | IEC<br>UL<br>CSA<br>EAC<br>ABS<br>ATEX INERIS<br>UKCA  |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 5.59 cm  |
| Package 1 Width              | 10.16 cm |
| Package 1 Length             | 8.13 cm  |
| Package 1 Weight             | 0.18 kg  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

|                           |   |
|---------------------------|---|
| Reach Regulation          | <a href="#">REACH Declaration</a>   |
| Eu Rohs Directive         | Compliant with Exemptions   |
| China Rohs Regulation     | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information   |
| Environmental Disclosure  | <a href="#">Product Environmental Profile</a>   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| Circularity Profile       | <a href="#">End of Life Information</a>   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="#">www.P65Warnings.ca.gov</a> |