

carriage switches, drawout ComPact NSX, chassis connected (CE)/ disconnected (CD) position, 2 changeover contact types

LV429287

Main

| Device Short Name | CE CD | |
|-----------------------------|--|--|
| Product Or Component Type | Carriage switch | |
| Device Application | Monitoring | |
| Range Compatibility | ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250 ComPact ComPact NSX400 ComPact ComPact NSX630 | |
| Signal Contacts Composition | 2 NO/NC | |

Complementary

| Complementary | |
|--|--|
| Auxiliary Contacts Type | Standard |
| Auxiliary Contacts Operation | CE/CD |
| Mounting Mode | Drawout |
| [Ith] Conventional Free Air Thermal Current | 6 A |
| [le] Rated Operational Current | AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz |
| | AC-12: 6 A at 24 V AC 50/60 Hz |
| | AC-12: 6 A at 380/440 V AC 50/60 Hz |
| | AC-12: 6 A at 48 V AC 50/60 Hz |
| | AC-12: 6 A at 480 V AC 50/60 Hz |
| | AC-12: 6 A at 660/690 V AC 50/60 Hz |
| | AC-15: 0.1 A at 660/690 V AC 50/60 Hz |
| | AC-15: 1.5 A at 480 V AC 50/60 Hz |
| | AC-15: 2 A at 380/440 V AC 50/60 Hz |
| | AC-15: 4 A at 220/240 V AC 50/60 Hz |
| | AC-15: 5 A at 110 V AC 50/60 Hz |
| | AC-15: 6 A at 24 V AC 50/60 Hz |
| | AC-15: 6 A at 48 V AC 50/60 Hz |
| | DC-12: 0.3 A at 250 V DC |
| | DC-12: 0.6 A at 110 V DC |
| | DC-12: 2.5 A at 48 V DC |
| | DC-12: 6 A at 24 V DC |
| | DC-14: 0.03 A at 250 V DC |
| | DC-14: 0.05 A at 110 V DC |
| | DC-14: 0.2 A at 48 V DC |
| | DC-14: 1 A at 24 V DC |
| Minimum Load | 100 mA at 24 V DC |
| Quantity Per Set | 2 |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1 |

| Package 1 Height | 3.9 cm |
|------------------------------|----------|
| Package 1 Width | 6.1 cm |
| Package 1 Length | 8.0 cm |
| Package 1 Weight | 54.0 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 45 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 2.737 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
|----------------------------|---|
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| Reach Regulation | REACh Declaration |
| Rohs Exemption Information | Yes |
| Mercury Free | |
| Toxic Heavy Metal Free | |
| Reach Free Of Svhc | |