



Main

Range	Linery
Product name	BZ
Device short name	LA9Z
Product or component type	Adaptors for busbar systems
Number of ways	1 way

Complementary

Range compatibility	Prisma - G Prisma - P Compact Prisma - PH Spacial
Product compatibility	NSX400...630
Poles description	4P
Permissible current	200 A with 12 x 5 mm busbar 250 A with 15 x 5 mm busbar 320 A with 20 x 5 mm busbar 400 A with 25 x 5 mm busbar 450 A with 30 x 5 mm busbar 360 A with 12 x 10 mm busbar 520 A with 20 x 10 mm busbar 630 A with 30 x 10 mm busbar
[Ui] rated insulation voltage	690 V
Busbar pitch	60 mm
Width	184 mm
Height	284 mm
Depth	63 mm
Colour	Anthracite grey

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

IP degree of protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1121 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations