Product data sheet

Specifications



current transformer module with voltage output, ComPact NSX400/630, 400A rating, 4 poles

LV432654

Main

Device Short Name	CT module and voltage output
Product Or Component Type	Current transformer
Device Application	Control
Range Compatibility	ComPact ComPact NSX400 ComPact ComPact NSX630 ComPact ComPacT INS ComPact Compact INV
Poles Description	4P
[In] Rated Current	400 A
Current Transformer Ratio	400/5 A
Power Consumption In Va	2 VA
Accuracy Class	Class 0.5

Complementary

[Ue] Rated Operational Voltage	530 V
Network Type	AC
Network Frequency	50/60 Hz
Auxiliary Connection Terminal	Cable connector 2.5 mm ²

Environment

Electrical Shock Protection Class	Class II
Ip Degree Of Protection	IP40 conforming to IEC 60529
Ik Degree Of Protection	IK04 conforming to IEC 62262

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	17.0 cm
Package 1 Length	20.0 cm
Package 1 Weight	2.595 kg
Unit Type Of Package 2	S03
Number Of Units In Package 2	2

Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.677 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information