# Product data sheet

Specifications



① Discontinued

# blown fuse indicator 4P(only for DIN type)- 4NO or NC- for Fupact INF200 to 800

LV480559

() Discontinued on: Dec 1, 2021

#### Main

Range Of Product   INF200800     Range   FuPact     Device Short Name   blown fuse indicator     Product Or Component Type   Blown Fuse Indicator     Device Application   Display     Range Compatibility   FuPact Fupact INF fuse-switch disconnector     Poles Description   4 NC     4 NO   4 NO	
Device Short Name blown fuse indicator   Product Or Component Type Blown Fuse Indicator   Device Application Display   Range Compatibility FuPact Fupact INF fuse-switch disconnector   Poles Description 4P   Signal Contacts Composition 4 NC	
Product Or Component Type Blown Fuse Indicator   Device Application Display   Range Compatibility FuPact Fupact INF fuse-switch disconnector   Poles Description 4P   Signal Contacts Composition 4 NC	
Device Application Display   Range Compatibility FuPact Fupact INF fuse-switch disconnector   Poles Description 4P   Signal Contacts Composition 4 NC	
Range Compatibility FuPact Fupact INF fuse-switch disconnector   Poles Description 4P   Signal Contacts Composition 4 NC	
Poles Description 4P   Signal Contacts Composition 4 NC	
Signal Contacts Composition 4 NC	
• • • • • • • • • • • • • • • • • • • •	
4 NU	

## Complementary

[Ith] Conventional Free Air Thermal Current	16 A
[le] Rated Operational Current	DC-12: 0.55 A at 250 V DC
	DC-12: 0.1 A at 380/415 V DC
	DC-12: 0.1 A at 440 V DC
	DC-12: 0.55 A at 220/240 V DC
	AC-15: 2 A at 660/690 V AC
	AC-15: 4 A at 380/415 V AC
	AC-15: 6 A at 110 V AC
	AC-15: 6 A at 220/240 V AC
	AC-15: 6 A at 24 V AC
	AC-15: 6 A at 250 V AC
	AC-15: 6 A at 48 V AC
	DC-12: 10 A at 24 V DC
	DC-12: 2 A at 110 V DC
	DC-12: 4 A at 48 V DC
	DC-13: 0.27 A at 250 V DC
	DC-13: 0.55 A at 110 V DC
	DC-13: 0.8 A at 48 V DC
	DC-13: 2 A at 24 V DC
Minimum Load	10 mA at 24 V

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.6 cm
Package 1 Width	11.4 cm
Package 1 Length	44.9 cm
Package 1 Weight	203 g

# **Contractual warranty**

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Êà

#### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile