

TeSys F - contactor coil - LX4FX - 220 V DC

LX4FX220

! Discontinued on: Sep 7, 2021

! Discontinued

Main

Range	TeSys	
Product Or Component Type	Contactor coil	
Device Short Name	LX4FX	
Range Compatibility	TeSys TeSys F LC1F contactor	
Product Compatibility	LC1F780	
Control Circuit Type	DC low consumption	
[Uc] Control Circuit Voltage	220 V DC	
Inductance Of Closed Circuit	1 H	
Average Resistance	24.6 Ohm inrush at 20 °C 1100 Ohm holding at 20 °C	
Operating Time	100130 ms opening 7080 ms closing	
Mechanical Durability	ty 5 Mcycles	
Maximum Operating Rate	600 cyc/h 55 °C	

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational: 0.851.1 Uc (at 55 °C) Drop-out: 0.20.4 Uc (at 55 °C)
Inrush Power In W	2000 W (at 20 °C)
Hold-In Power Consumption In W	42 W at 20 °C

Environment

Ambient Air Temperature For Operation	-555 °C
Net Weight	3 kg
Quantity Per Set	Set of 2

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	18.5 cm

Package 1 Length	25 cm	
Package 1 Weight	3.011 kg	

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope)
		EU RoHS Declaration
Chin	na Rohs Regulation	China RoHS declaration