

current transformer tropicalised DIN mount 100 5 for cables d. 21

METSECT5CC010

Main

| Range | PowerLogic |
|---------------------------|---|
| Product Name | СТ |
| Product Or Component Type | Current transformer |
| Secondary Current | 5 A |
| Accuracy Class | Class 0.5 at 2 VA Class 1 at 2.5 VA Class 3 at 3.5 VA |
| [In] Rated Current | 100 A |

Complementary

| Current Transformer Type | Tropicalised for cable |
|--|------------------------------|
| Current Transformer Ratio | 100/5 |
| [Ith] Conventional Free Air Thermal Current | 6 kA |
| Dynamic Withstand Current | 2.5 lth |
| Maximum Safety Factor | 5 |
| [Ue] Rated Operational Voltage | < 720 V AC 50/60 Hz |
| [Ui] Rated Insulation Voltage | 3 kV |
| Mounting Mode | By screws Clip-on |
| Mounting Support | Mounting plate DIN rail |
| Width | Outside: 44 mm |
| Height | Outside: 65 mm |
| Depth | 30 mm frame: 37 mm total: |
| Diameter | 21 mm |
| Net Weight | 0.19 kg |
| [Uimp] Rated Impulse Withstand Voltage | 3 kV |
| Electrical Insulation Class | Class B |
| Cable Outer Diameter | 21 mm |
| Sealing | With |

Environment

| Standards | VDE 0414 IEC 61869-2 |
|---------------------------------------|-------------------------|
| Product Certifications | EAC CE |
| Ip Degree Of Protection | IP20 |
| Relative Humidity | 095 % |
| Ambient Air Temperature For Operation | -2560 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.600 cm |
| Package 1 Width | 5.600 cm |
| Package 1 Length | 8.400 cm |
| Package 1 Weight | 192.000 g |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 50 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 9.864 kg |
| Unit Type Of Package 3 | P12 |
| Number Of Units In Package 3 | 400 |
| Package 3 Height | 27.500 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 88.800 kg |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
|-----------------------|---|
| China Rohs Regulation | China RoHS declaration |
| Eu Rohs Directive | Compliant with Exemptions |
| Reach Regulation | REACh Declaration |