

current transformer tropicalised 1500 5 double output for bars 38x127

METSECT5DB150

Main

Range	PowerLogic
Product Name	СТ
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 10 VA Class 1 at 15 VA
[In] Rated Current	1500 A

Complementary

Tropicalised for busbar
1500/5
60 kA
2.5 lth
5
< 720 V AC 50/60 Hz
3 kV
Insulated locking screw
Busbar
38 mm inner: 99 mm outside:
127 mm inner: 160 mm outside:
40 mm frame: 78.4 mm total:
0.805 kg
3 kV
Class B
127 x 38
127 X 30

Environment

Standards	IEC 61869-2
	VDE 0414

Product Certifications	EAC CE
Ip Degree Of Protection	IP20
Relative Humidity	095 %
Ambient Air Temperature For Operation	-2550 °C
Packing Units	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.6 cm
Package 1 Width	10.4 cm
Package 1 Length	17.2 cm
Package 1 Weight	775.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	10
Package 2 Height	30.0 cm

30.0 cm

40.0 cm

8.477 kg

Package 2 Width
Package 2 Length

Package 2 Weight

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
China Rohs Regulation	China RoHS declaration
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration