# Product data sheet

Specifications



() Discontinued

# Unica Plus - 2 complete S.O. -2P+E, shutters, PO/FR - 4 m - ivory/ sand

MGU63.069.567

- () Discontinued on: Jul 26, 2021
- (!) End-of-service on: Feb 2, 2022

#### Main

| Range                       | Unica              |
|-----------------------------|--------------------|
| Product Or Component Type   | Socket-outlet      |
| Aesthetic Name              | Unica Plus         |
| Device Presentation         | Complete mechanism |
| Device Mounting             | Flush              |
| Socket Number               | 2                  |
| Outlet Poles Configuration  | 2P + E             |
| Outlet Standard             | Poland<br>French   |
| Outlet Standard Description | Displaced earth    |
| Rated Current               | 16 A               |

### Complementary

| Device Application             | Power supply                                                                    |
|--------------------------------|---------------------------------------------------------------------------------|
| Cover Type                     | With shutter                                                                    |
| [Ue] Rated Operational Voltage | 250 V                                                                           |
| Network Type                   | AC                                                                              |
| Network Frequency              | 50/60 Hz                                                                        |
| Number Of Modules              | 4 modules                                                                       |
| Fixing Mode                    | Short claws                                                                     |
| Colour Tint                    | lvory                                                                           |
| Connections - Terminals        | Screw terminals                                                                 |
| Cable Cross Section            | 04 mm² - cable stiffness: flexible<br>04 mm² - cable stiffness: rigid           |
| Minimum Load Breaking Capacity | 100 operations 1.25 In and 1.1 Un, cos phi = 0.6                                |
| Electrical Durability          | 10000 cycles, cos phi = 0.8                                                     |
| Insulation Resistance          | > 5 MOhm at 500 V                                                               |
| Dielectric Strength            | 2000 V                                                                          |
| Material                       | ASA + PC: mechanism cover<br>ABS (acrylonitrile butadiene-styrene): cover frame |
| Quantity Per Set               | Set of 1 box                                                                    |

| Embedding Depth | 27 mm     |
|-----------------|-----------|
| Depth           | 37 mm     |
| Width           | 90.21 mm  |
| Height          | 122.9 mm  |
| Net Weight      | 0.1281 kg |

### Environment

| Ambient Air Temperature For<br>Operation | 1530 °C                                                                                               |
|------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature For<br>Storage   | 035 °C                                                                                                |
| Ik Degree Of Protection                  | IK01                                                                                                  |
| Ip Degree Of Protection                  | IP20                                                                                                  |
| Environmental Characteristic             | Petrol<br>Acetone<br>Liquid soap<br>Oil<br>UV resistant<br>Alcohol<br>Window-cleaning fluid<br>Bleach |

# **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 9 cm    |
| Package 1 Width              | 12.2 cm |
| Package 1 Length             | 4.7 cm  |
| Package 1 Weight             | 129 g   |

# **Contractual warranty**

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

Fa

|              | Toxic Heavy Metal Free     |     |
|--------------|----------------------------|-----|
|              | Mercury Free               |     |
| $\checkmark$ | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration                                                                                                           |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration                                                                                            |
| China Rohs Regulation    | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                 |
| Environmental Disclosure | Product Environmental Profile                                                                                               |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations                                                                                    |