

# Product data sheet

Specifications



Mom./maint.cont. switch insrt f. roller shut.s f.cyl. locks, alum., Anti-Vanda.

MTN318260

! Discontinued on: Dec 15, 2023

! Discontinued

## Main

Range Of Product	Merten Anti-vandalism
Aesthetic Name	Anti-vandalism
Product Or Component Type	Push-button
Device Presentation	Complete mechanism

## Complementary

Switch Function	2-pole
Control Type	Key
Device Mounting	Flush
Fixing Mode	By screws and claws
[Ue] Rated Operational Voltage	250 V
Maximum Switching Current	10 mA
Material	Aluminium matt

## Environment

Surface Treatment	Teflon coated Metallic
Ip Degree Of Protection	IP44

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	10.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	318.0 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	21
Package 2 Height	18.5 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Weight	7.52 kg
------------------	---------

## Contractual warranty

Warranty	18 months
----------	-----------

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



## Transparency

Eu Rohs Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations