


Product data sheet

Specifications



Blanking plug for cable entry grommet Multi-CS, for cables diameters 2-12

NSYCEJDS0

Main

Range	Spacial
Product Or Component Type	Blanking plug
Accessory / Separate Part Category	Cable management accessory
Device Application	Multi-purpose
Quantity Per Set	Set of 12

Complementary

Material	TPE (thermoplastic elastomer)
Cable Entry Number	1 x 2...12 mm
Net Weight	0.006 kg

Environment

Ip Degree Of Protection	IP65 conforming to IEC 60529
Flame Retardance	V0 conforming to UL 94
Ambient Air Temperature For Operation	-30...100 °C
Resistance To Chemical Agents	Good resistance to mineral oils and greases Good resistance to fuels Good resistance to weak acids and bases Good resistant to alcohols

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	2.0 cm
Package 1 Length	2.0 cm
Package 1 Weight	5.0 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations