

## ClimaSys indoor slim cooling unit block - 2000W at 460 V - UL

NSYCUS2K3P4UL

- ! To be discontinued on: Dec 31, 2024
- ! To be end-of-service on: Dec 31, 2026

#### Main

Range	ClimaSys
Product Name	CU
Product Or Component Type	Slim cooling unit block
Mounting Type	Door of enclosure
Installation	Indoor side
Product Destination	For enclosure
Mounting Mode	By screws
Supply Voltage	460 V AC at 60 Hz, 3 phases
Rated Power	2300 W
Cooling Power	6824 Btu/h 60 Hz L35-L35 5289 Btu/h 60 Hz L35-L50

## Complementary

Height	1696 mm
Width	495 mm
Depth	195 mm
[In] Rated Current	2.1 A
Inrush Current	10 A
Power Consumption In W	1060 W at 60 Hz, L35-L35 1270 W at 60 Hz, L35-L50
Energy Efficiency Ratio	1.9
Control Type	Electronic controller
Temperature Setting Range	2050 °C
Ambient Air Temperature For Operation	50 °C maximum: 2046 °C inside the enclosure: 2050 °C outside the enclosure:
Noise Level	67 dB conforming to EN/ISO 3746
Pressure	28 bar
Flow Rate	External circuit: 1050 m3/h at 60 Hz Internal circuit: 860 m3/h at 60 Hz
Net Weight	65 kg
Cooling Gas Type	R134a (0.59 kg)
Type Of Filter	Optional external circuit filter

Protection Type	Thermal protection: T 6 A Short-circuit protection (magnetic):
Material	Steel
Colour	Grey (RAL 7035)

# **Environment**

Product Certifications	UL
Ip Degree Of Protection	IP55 conforming to IEC 60529 (on the internal circuit) IP34 conforming to IEC 60529 (on the external circuit)

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	19.5 cm
Package 1 Width	49.5 cm
Package 1 Length	169.6 cm
Package 1 Weight	65.0 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	2
Package 2 Height	206.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	195.0 kg

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information
Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information