Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Metallic mounting plate for PLA enclosure H1250xW500mm

NSYPMM125

Main

Range	Thalassa
Accessory / Separate Part Category	Mounting accessory
Product Or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure Nominal Dimensions	-
Mounting Location	Back inserts Step slide
Mounting Plate Description	Plain
Range Compatibility	Thalassa Thalassa PLA Thalassa Thalassa PHD
Device Composition	1 mounting plate
Material	Galvanised steel

Complementary

Fixing Mode	By screws - screw type M8 - on back inserts location
Permanent Permissible Load	150 kg
Height	1250 mm nominal: 1140 mm real:
Width	500 mm nominal: 375 mm real:
Depth	125 mm real:
Thickness	2.5 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.3 cm
Package 1 Width	40.0 cm
Package 1 Length	115.0 cm
Package 1 Weight	8.47 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations