

Safety terminals section 1x35mm². Supply: 20

NSYS2535

Main

Accessory / Separate Part Category	Power distribution
Product Or Component Type	Safety terminal
Device Application	Multi-purpose
Range Compatibility	Spacial Thalassa
Device Composition	1 sigma terminal
Quantity Per Set	Set of 20
Nominal Cross Section	35 mm² 1

Complementary

Mounting Location	On mounting accessories
Material	Polyamide 6 matt black for base Polypropylene orange for cover MS-58 brass for terminal Zinc-plated and dichromated steel for ring
Height	38 mm
Width	23 mm
Depth	46 mm
Diameter	23 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	4.000 cm
Package 1 Length	4.500 cm
Package 1 Weight	29.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	20
Package 2 Height	4.000 cm
Package 2 Width	13.500 cm
Package 2 Length	17.000 cm
Package 2 Weight	625.000 g

Unit Type Of Package 3	S04
Number Of Units In Package 3	560
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	18.160 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations