



Main

Range	Actassi
Product name	Actassi VDC
Product or component type	19" enclosure
Device application	Cabling
Applications	To protect network connectivity equipment To mount 19" equipment
Enclosure type	1 body
Front face	Glazed door
Colour	Light grey (RAL 7035)
Installation mode	Wall mounted

Complementary

Support equipment	2 x 19" uprights recessed of 120 mm from the front (pitch 25 mm)
Door type	Front glazed door - with 1 point locking system (key: 333) - reversible opening at 120 °
Accessibility for operation	Front
Removable parts	Front door removable toolless
Device composition	1 x front glazed door
Load rating	Static : 50 kg
Number of cut-out	1 cut-out bottom
Material	Structure : sheet steel
Surface finish	Epoxy-polyester powder
Enclosure nominal dimensions	- 450 mm 600 mm 400 mm
Number of rack unit	9U
Targeted region	Europe

Environment

IK degree of protection	IK08 conforming to IEC 62262
-------------------------	------------------------------

IP degree of protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant Schneider Electric declaration of conformity
------------------------	---

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

Product environmental profile	Available Product Environmental Profile
-------------------------------	--

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
