Product data sheet

Specifications

Polyester glassreinforced plinth for encl. PLM86 front opening IP44-IK10 RAL7035

NSYZM263G

Main

Range	Thalassa
Accessory / Separate Part Category	Enclosure accessory
Product Or Component Type	Plinth
Application	Multi-purpose
Nominal Dimensions Of The Housing	-
Device Composition	fixing elements 2 front panel 2 side part
Range Compatibility	Thalassa Thalassa PLM

Complementary

Fixing Mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 mm
Width	556 mm
Depth	302 mm

Environment

Ip Degree Of Protection	IP44
Ik Degree Of Protection	IK10

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18.0 cm
Package 1 Width	22.0 cm
Package 1 Length	60.5 cm
Package 1 Weight	7.15 kg
Unit Type Of Package 2	PAM
Number Of Units In Package 2	50
Package 2 Height	120 cm
Package 2 Width	100 cm
Package 2 Length	122 cm

Package 2 Weight   360 kg

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation   China RoHS declaration

                                   Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure   Product Environmental Profile

Circularity Profile   No need of specific recycling operations