

Exiway Power Control Pico - central battery system - 4 Main cts 80 lum (Max)

OVA18046

Main

| Range | Exiway |
|---------------------------|------------------------------|
| | |
| Product Name | Exiway Power Control |
| Device Short Name | Exiway Power Control Pico |
| Product Or Component Type | Central battery system |
| Number Of Circuits | 4 |
| Number Of Light Blocks | 80 |
| Device Composition | 2 main circuit module |
| Supply | Maintained Non-maintained |

Complementary

| <u>Complementary</u> | |
|---------------------------------------|--|
| [Us] Rated Supply Voltage | 230 V 50 Hz |
| Poles Description | 1P |
| Output Voltage | 230 V AC |
| | 216 V DC |
| Rated Power In W | 500 W 1 h 2.3 A |
| | 200 W 3 h 0.93 A |
| | 80 W 8 h 0.37 A |
| Rated Power In Va | 2000 VA |
| Number Of Batteries | 18 12 V 5.2 Ah |
| Display Type | LCD display |
| Communication Network Type | Ethernet TCP/IP |
| Communication Port Support | RS232 |
| | RS485 |
| Communication Port Protocol | Modbus |
| Web Services | Web server |
| Language | Multi-language |
| Cover Type | Lockable cover to be ordered separately |
| Battery Type | Lead-acid battery |
| Charging Time | 12 h 80 % autonomy |
| Provided Equipment | Light switch query module MMO internal |
| | I/O module internal |
| | Battery temperature sensor |
| | Critical circuit interface module internal |
| Ambient Air Temperature For Operation | 035 °C |

| Material | Sheet steel |
|---------------|-------------|
| Maximum Power | 500 W |

Environment

| <u> </u> | |
|-----------------------------|------------------|
| Colour | Grey |
| Colour Code | RAL 7035 |
| Ip Degree Of Protection | IP20 |
| Mounting Mode | Floor-standing |
| | Wall-mounted |
| Electrical Insulation Class | Class I |
| Standards | EN 55015 |
| | EN 50171 |
| | EN 61000-3-3 |
| | IEC 60364-5-56 |
| | EN 61000-3-2 |
| | DIN VDE 0108-100 |
| | EN 50172 |
| | EN 50272-2 |
| | DIN VDE 0100-718 |
| | EN 61547 |
| Height | 630 mm |
| Width | 350 mm |
| Depth | 230 mm |
| Net Weight | 55 kg |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 35.0 cm |
| Package 1 Width | 63.0 cm |
| Package 1 Length | 23.0 cm |
| Package 1 Weight | 85.5 kg |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Under investigation