Specifications



Socket, Mureva PK, wall-mounted, angled, 32A, 2P+E, 220V, IP67

PKF32W723

Main

Range	Mureva
Product Or Component Type	Socket
Device Short Name	Mureva socket
Plug, Socket Category	Low voltage
Poles Description	2P + E
Network Type	AC
Outlet Standard	Industrial

Complementary

Plug, Socket, Control Station Shape Angled Plug, Socket, Control Station Shape Angled In] Rated Current 32 A (Ue] Rated Operational Voltage 200250 V Network Frequency 50/60 Hz Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Plug, Socket, Control Station Shape Angled [In] Rated Current 32 A [Ue] Rated Operational Voltage 200250 V Network Frequency 50/60 Hz Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm	· · · · · · · · · · · · · · · · · · ·	
Shape32 A[In] Rated Current32 A[Ue] Rated Operational Voltage200250 VNetwork Frequency50/60 HzGround Lug Clockwise Position6 hPlug, Socket MaterialHousing: self-extinguishing engineering polymerContacts MaterialSleeves: brassConnections - TerminalsCaptive screwsCable Outer Diameter21 mmThread TypeM25Height191 mmWidth106 mmDepth148 mmColourGrey (RAL 7035)	Shape32 A[In] Rated Current32 A[Ue] Rated Operational Voltage200250 VNetwork Frequency50/60 HzGround Lug Clockwise Position6 hPlug, Socket MaterialHousing: self-extinguishing engineering polymerContacts MaterialSleeves: brassConnections - TerminalsCaptive screwsCable Outer Diameter21 mmThread TypeM25Height191 mmWidth106 mmDepth148 mmColourGrey (RAL 7035)	Mounting Mode	Wall-mounted
Image: Constant of the second secon	[Ue] Rated Operational Voltage 200250 V Network Frequency 50/60 Hz Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)		Angled
Network Frequency 50/60 Hz Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Network Frequency 50/60 Hz Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	[In] Rated Current	32 A
Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Ground Lug Clockwise Position 6 h Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	[Ue] Rated Operational Voltage	200250 V
Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Plug, Socket Material Housing: self-extinguishing engineering polymer Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Network Frequency	50/60 Hz
Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Contacts Material Sleeves: brass Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Ground Lug Clockwise Position	6 h
Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Connections - Terminals Captive screws Cable Cross Section 2.510 mm² Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Plug, Socket Material	Housing: self-extinguishing engineering polymer
Cable Cross Section2.510 mm²Cable Outer Diameter21 mmThread TypeM25Height191 mmWidth106 mmDepth148 mmColourGrey (RAL 7035)	Cable Cross Section2.510 mm²Cable Outer Diameter21 mmThread TypeM25Height191 mmWidth106 mmDepth148 mmColourGrey (RAL 7035)	Contacts Material	Sleeves: brass
Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Cable Outer Diameter 21 mm Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Connections - Terminals	Captive screws
Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Thread Type M25 Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Cable Cross Section	2.510 mm ²
Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Height 191 mm Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Cable Outer Diameter	21 mm
Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Width 106 mm Depth 148 mm Colour Grey (RAL 7035)	Thread Type	M25
Depth 148 mm Colour Grey (RAL 7035)	Depth 148 mm Colour Grey (RAL 7035)	Height	191 mm
Colour Grey (RAL 7035)	Colour Grey (RAL 7035)	Width	106 mm
		Depth	148 mm
	Voltage Colour Blue	Colour	Grey (RAL 7035)
blue blue		Voltage Colour	Blue

Environment

Standards	IEC 60309-2 IEC 60309-1
Ip Degree Of Protection	IP67 conforming to IEC 60529
Ik Degree Of Protection	IK08 conforming to EN 62262

Fire Resistance	750 °C conforming to IEC 60695-2-1
Relative Humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient Air Temperature For Operation	35 °C (86400 s) -25…40 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.4 cm
Package 1 Width	9.5 cm
Package 1 Length	16.1 cm
Package 1 Weight	310 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	17.6 cm
Package 2 Width	26.6 cm
Package 2 Length	27 cm
Package 2 Weight	1.74 kg
Unit Type Of Package 3	\$03
Number Of Units In Package 3	10
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	3.967 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eà

Transparency RoHS/REACh

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations