Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Resi9 - comb busbar - 1L - 18 mm pitch - 57 modules - 63 A

<u> որորդորդոր որորդորդոր</u>

R9XFH157

Main

Range	Resi9
Product Or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / Separate Part Category	Connection accessory
Lines Description	1L
Length In 18 Mm Modules	57

Complementary Number Of Ways

Number Of Ways	57 ways 1 L	
Poles Configuration For 1 Way	1 x 1P	
Connection Pitch	18 mm	
Connector Type	Fork	
Distance Between Way	18 mm	
Marking	L	
Insulation	Insulated	
Device Presentation	Cuttable	
[le] Rated Operational Current	63 A at 40 °C	
[Ue] Rated Operational Voltage	230 V AC Ph/N	
[Ui] Rated Insulation Voltage	500 V AC	
Mounting Location	Bottom on biconnect	
9 Mm Pitches	114	
Width	1000 mm	
Colour	White (RAL 9003)	
Range Compatibility	Acti 9 Acti9 K60 Resi9 Resi9 MCB Resi9 Resi9 RCBO Resi9 Resi9 RCCB Resi9 Resi9 SWITCH	

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Product Certifications	CE
Fire Resistance	960 °C (30 s) conforming to IEC 60695-2-1

Pollution Degree 3

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	1.500 cm
Package 1 Length	101.500 cm
Package 1 Weight	206.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	5.500 cm
Package 2 Width	106.500 cm
Package 2 Length	9.000 cm
Package 2 Weight	1.199 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	270
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	113.000 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc
 ✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations