



Main

Range of product	RelayAux
Product or component type	Time delay relay
[Uc] control circuit voltage	125 V AC/DC (- 30 % + 25 % Un)
Product compatibility	REL91350 (front connection socket) REL91357 (flush mounting socket)
Status LED	With
Local signalling	LED

Complementary

Contacts type and composition	4 C/O
Insulation resistance measurements	> 100 MOhm at 500 V DC conforming to IEC 60255-5
[Uimp] rated impulse withstand voltage	5 kV during 1.2/50 µs conforming to IEC 60255-5
Contacts material	AgNi
Permanent current	10 A
Instantaneous current	30 A during 1 s 80 A during 200 ms 200 A during 10 ms
Maximum making capacity	40 A during 0.5 s at 110 V DC 30 A during 1 s at 36 V DC
Mechanical durability	10000000 cycles
Average coil consumption	4 W
Pick-up time	23 ms
Drop-out time	40 ms
Maximum contact resistance	30 mOhm
Mechanical robustness	Shocks 11 ms (5 gn) conforming to IEC 60068-2-27 Bumps 16 ms (10 Gn) conforming to IEC 60068-2-29
Width	42.5 mm
Depth	96.6 mm
Net weight	0.265 kg

Environment

Dielectric strength	2 kV 50 Hz 1 min conforming to IEC 60255-5
---------------------	--

Maximum relative humidity	93 % at 40 °C
Electromagnetic compatibility	<p>Conducted and radiated emissions criteria A conforming to EN 55022</p> <p>Conducted and radiated emissions criteria B conforming to EN 55022</p> <p>Electrostatic discharge - test level: 15 kV level 4 (air discharge) conforming to IEC 61000-4-2</p> <p>Electrostatic discharge - test level: 8 kV level 4 (contact discharge) conforming to IEC 61000-4-2</p> <p>Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m, 80 MHz...1 GHz level 3 conforming to IEC 61000-4-3</p> <p>Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m, 80 MHz...1 GHz level 3 conforming to ENV 50204</p> <p>Electrical fast transient/burst immunity test - test level: 4 kV, 5 kHz level 4 (1 min) conforming to IEC 61000-4-4</p> <p>Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5</p> <p>Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC 61000-4-5</p> <p>Conducted RF disturbances - test level: 10 V, 0.15...80 MHz level 3 conforming to IEC 61000-4-6</p> <p>Magnetic field at power frequency - test level: 100 A/m level 5 (continuous) conforming to IEC 61000-4-8</p> <p>Magnetic field at power frequency - test level: 1000 A/m level 5 (2 s) conforming to IEC 61000-4-8</p> <p>Damped oscillating waves - test level: 2.5 kV, 1 MHz level 3 (common mode) conforming to IEC 60255-22-1</p> <p>Damped oscillating waves - test level: 1 kV, 1 MHz level 3 (differential mode) conforming to IEC 60255-22-1</p>
Climatic withstand	<p>Exposure to cold (in operation) : - 25 °C conforming to IEC 60068-2-1</p> <p>Exposure to cold (in storage) : - 25 °C conforming to IEC 60068-2-1</p> <p>Continuous exposure to damp heat (in storage) : 56 days, 93 % RH, 40 °C conforming to IEC 60068-2-78</p> <p>Salt mist (in storage) : 6 days conforming to ISO 9227</p> <p>Exposure to dry heat (in operation) : 55 °C conforming to IEC 60068-2-2</p> <p>Exposure to dry heat (in storage) : 55 °C conforming to IEC 60068-2-2</p>
Vibration resistance	<p>1 gn (f = 58...150 Hz) conforming to IEC 60068-2-1</p> <p>+/- 0.075 mm (f = 10...58 Hz) conforming to IEC 60068-2-1</p>
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-25...55 °C
Fire resistance	850 °C during 30 s
Operating altitude	< 2000 m
Directives	<p>72/23/EEC - low voltage directive</p> <p>92/31/EEC - electromagnetic compatibility</p> <p>89/336/EEC - electromagnetic compatibility</p> <p>93/68/EEC - low voltage directive</p>
Product certifications	<p>UL listed file E322124</p> <p>CE</p> <p>RoHS</p>
Height	50.4 mm