## Product data sheet

Specifications



# Orion - cover & fixing-frame 4X2 - 2 modules - ivory

S735121014

() Discontinued on: Jun 30, 2023

#### Main

| Range                     | Orion         |
|---------------------------|---------------|
| Aesthetic Name            | Orion Essence |
| Product Or Component Type | Cover frame   |

#### Complementary

| Device MountingFlushProvided EquipmentFixing frameNumber Of Gangs2 gangsNumber Of Modules2 x 1 moduleFixing ModeClip-inColour TintIvory (RAL 1013)Surface FinishGlossySurface TreatmentUntreatedType Of PackingFlow-packQuantity Per SetSet of 30Ambient Air Temperature For<br>Operation-550 °CAmbient Air Temperature For<br>Operation-535 °CMaterialThermoplastic ABS-UV stabilised: decorative frameHeight120 mmWidth82.5 mm                    | bompicinental y       |                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--------------------------------------------------|
| Number Of Gangs2 gangsNumber Of Modules2 x 1 moduleFixing ModeClip-inColour TintIvory (RAL 1013)Surface FinishGlossySurface TreatmentUntreatedType Of PackingFlow-packQuantity Per SetSet of 30Ambient Air Temperature For<br>Operation-535 °CAmbient Air Temperature For<br>Operation-535 °CMaterialThermoplastic ABS-UV stabilised: decorative frameHeight120 mmWidth82.5 mm                                                                      | evice Mounting Flu    | ush                                              |
| Number Of Modules   2 x 1 module     Fixing Mode   Clip-in     Colour Tint   Ivory (RAL 1013)     Surface Finish   Glossy     Surface Treatment   Untreated     Type Of Packing   Flow-pack     Quantity Per Set   Set of 30     Ambient Air Temperature For<br>Operation   -550 °C     Ambient Air Temperature For<br>Operation   -535 °C     Material   Thermoplastic ABS-UV stabilised: decorative frame     Height   120 mm     Width   82.5 mm | rovided Equipment Fix | xing frame                                       |
| Fixing Mode   Clip-in     Colour Tint   Ivory (RAL 1013)     Surface Finish   Glossy     Surface Treatment   Untreated     Type Of Packing   Flow-pack     Quantity Per Set   Set of 30     Ambient Air Temperature For<br>Storage   -550 °C     Ambient Air Temperature For<br>Operation   -535 °C     Material   Thermoplastic ABS-UV stabilised: decorative frame     Height   120 mm     Width   82.5 mm                                        | umber Of Gangs 2 g    | gangs                                            |
| Colour TintIvory (RAL 1013)Surface FinishGlossySurface TreatmentUntreatedType Of PackingFlow-packQuantity Per SetSet of 30Ambient Air Temperature For<br>Storage-550 °CAmbient Air Temperature For<br>Operation-535 °CMaterialThermoplastic ABS-UV stabilised: decorative frameHeight120 mmWidth82.5 mm                                                                                                                                             | umber Of Modules 2 >  | x 1 module                                       |
| Surface Finish   Glossy     Surface Treatment   Untreated     Type Of Packing   Flow-pack     Quantity Per Set   Set of 30     Ambient Air Temperature For<br>Storage   -550 °C     Ambient Air Temperature For<br>Operation   -535 °C     Material   Thermoplastic ABS-UV stabilised: decorative frame     Height   120 mm     Width   82.5 mm                                                                                                     | ixing Mode Cli        | lip-in                                           |
| Surface Treatment Untreated   Type Of Packing Flow-pack   Quantity Per Set Set of 30   Ambient Air Temperature For<br>Storage -550 °C   Ambient Air Temperature For<br>Operation -535 °C   Material Thermoplastic ABS-UV stabilised: decorative frame   Height 120 mm   Width 82.5 mm                                                                                                                                                               | olour Tint Ivo        | ory (RAL 1013)                                   |
| Type Of Packing Flow-pack   Quantity Per Set Set of 30   Ambient Air Temperature For<br>Storage -550 °C   Ambient Air Temperature For<br>Operation -535 °C   Material Thermoplastic ABS-UV stabilised: decorative frame   Height 120 mm   Width 82.5 mm                                                                                                                                                                                             | urface Finish GI      | lossy                                            |
| Quantity Per Set Set of 30   Ambient Air Temperature For<br>Storage -550 °C   Ambient Air Temperature For<br>Operation -535 °C   Material Thermoplastic ABS-UV stabilised: decorative frame   Height 120 mm   Width 82.5 mm                                                                                                                                                                                                                         | urface Treatment Ur   | ntreated                                         |
| Ambient Air Temperature For<br>Storage   -550 °C     Ambient Air Temperature For<br>Operation   -535 °C     Material   Thermoplastic ABS-UV stabilised: decorative frame     Height   120 mm     Width   82.5 mm                                                                                                                                                                                                                                    | ype Of Packing Flo    |                                                  |
| Storage   Ambient Air Temperature For<br>Operation -535 °C   Material Thermoplastic ABS-UV stabilised: decorative frame   Height 120 mm   Width 82.5 mm                                                                                                                                                                                                                                                                                             | uantity Per Set Se    | et of 30                                         |
| Operation Thermoplastic ABS-UV stabilised: decorative frame   Height 120 mm   Width 82.5 mm                                                                                                                                                                                                                                                                                                                                                         |                       | 50 °C                                            |
| Height 120 mm   Width 82.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                       |                       | 35 °C                                            |
| Width 82.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                       | laterial Th           | nermoplastic ABS-UV stabilised: decorative frame |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                     | eight 12              |                                                  |
| Denth 10.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                       | /idth 82              | 2.5 mm                                           |
| 18.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                             | epth 19               | 9.5 mm                                           |
| Net Weight 0.0363 kg                                                                                                                                                                                                                                                                                                                                                                                                                                | et Weight 0.0         | 0363 kg                                          |

#### Environment

| Ik Degree Of Protection | IK07  |
|-------------------------|-------|
| Ip Degree Of Protection | IP21D |

#### Hydrogen peroxide (H2O2) Oil Alcohol Window-cleaning fluid Bleach Petrol UV resistant Liquid soap Acetone

### **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 2.0 cm   |
| Package 1 Width              | 9.3 cm   |
| Package 1 Length             | 20.0 cm  |
| Package 1 Weight             | 0.038 kg |

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

| Eu Rohs Directive        | Under investigation                      |
|--------------------------|------------------------------------------|
| Environmental Disclosure | Product Environmental Profile            |
| Circularity Profile      | No need of specific recycling operations |