


Product data sheet

Specifications



Séquence5 - emergency light - 230V AC - 2 m - LED - Copper

S800001CS

⚠ Discontinued on: Jul 26, 2021

⚠ End-of-service on: Aug 19, 2021

⚠ Discontinued

Main

Aesthetic Name	Sequence5
Product Or Component Type	Emergency light
Device Presentation	Complete product
[Ue] Rated Operational Voltage	230 V AC +/- 10 % at 50 Hz

Complementary

Light Block Colour	Blue
Bulb Type	LED
Luminous Flux	145 lm
Colour Tint	Copper
Surface Finish	Glossy
Ambient Air Temperature For Operation	-20...40 °C
Ambient Air Temperature For Storage	-20...40 °C
Depth	43.5 mm
Width	115 mm
Height	80 mm
Net Weight	0.321 kg

Environment

Ip Degree Of Protection	IP20
-------------------------	------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5 cm
Package 1 Width	12 cm
Package 1 Length	18 cm
Package 1 Weight	376 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration	Product out of China RoHS scope. Substance declaration for your information