

Product data sheet

Specifications



Séquence5 - Combined Sockets SO + TV Copper

S800420CS

⚠ Discontinued on: Jul 26, 2021

⚠ End-of-service on: Aug 19, 2021

⚠ Discontinued

Main

Range	Sequence5
Product Or Component Type	Multi-services socket
Device Mounting	Flush
Fixing Mode	By screws
Colour Tint	Copper
Type Of Packing	Box
Quantity Per Set	Set of 1
Sale Per Indivisible Quantity	1

Complementary

Device Presentation	Complete product
Outlet Poles Configuration (Socket-Outlet)	2P + E with shutters
Outlet Standard Description (Socket-Outlet)	Pin earth
Outlet Standard (Socket-Outlet)	French
Rated Current (Socket-Outlet)	16 A at 250 V AC 50 Hz
Dielectric Strength (Socket-Outlet)	2000 V
Service Life In Cycles (Socket-Outlet)	5000 cycles
Electrical Durability (Socket-Outlet)	5000 cycles
Number Of Terminals (Socket-Outlet)	3
Clamping Connection Capacity (Socket-Outlet)	1 x 1.5...2 x 4 mm ² for rigid cable(s) 1 x 1.5...2 x 4 mm ² for stranded cable(s) 1 x 1.5...2 x 4 mm ² for flexible cable(s)
Tv Connector (Tv)	Male IEC 9.52 mm
Path Attenuation (Tv)	1.5 dB TV signal5...1800 MHz 2.5 dB TV signal1800...2150 MHz
Type Of Cable (Tv)	Coaxial
Shape Of Screw Head	TV module pozidriv No 1 Socket-outlet pozidriv No 1
Cable Outer Diameter	TV module 7 mm
Device Composition	Socket-outlet ASA + PC mechanism cover Socket-outlet PC (polycarbonate) GF10 FR casing TV module zinc alloy casing

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Surface Finish	Glossy
Width	160 mm
Height	80 mm
Depth	39.5 mm
Embedding Depth	35 mm
Net Weight	0.548 kg

Environment

Ik Degree Of Protection	IK04
Ip Degree Of Protection	IP21D
Ambient Air Temperature For Operation	Socket-outlet 5...35 °C TV module 5...45 °C
Ambient Air Temperature For Storage	-5...50 °C
Standards	EN 50083-4 NF C 61-314
Product Certifications	LCIE: NF 603415A NF
Environmental Characteristic	Petrol Acetone UV resistant Oil Bleach Window-cleaning fluid Liquid soap Alcohol

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5 cm
Package 1 Width	12 cm
Package 1 Length	18 cm
Package 1 Weight	603 g

Sustainability



Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	