

## automatic PowerLogic PFC Capacitor base, 550kvar 400-415V/ 50Hz

VLVB161

#### Main

| Network Rated Voltage | 400 V AC 50 Hz<br>415 V AC 50 Hz |
|-----------------------|----------------------------------|
| Reactive Power Rating | 550 kvar                         |
| Operating Mode        | Automatic                        |
| Range Of Product      | PowerLogic                       |
| Device Short Name     | automatic capacitor bank         |

## Complementary

| Network Pollution Level                | Low polluted                                                          |
|----------------------------------------|-----------------------------------------------------------------------|
| [Gh/Sn] Harmonic Pollution Rate        | 025 %                                                                 |
| [Thdu] Total Harmonic Distorsion       | 05 %                                                                  |
| Step Sequences                         | 1.2.2                                                                 |
| Power Per Step                         | 50 kvar                                                               |
| Step Composition                       | 50 + 5x100                                                            |
| Capacitor Technology                   | HDuty                                                                 |
| Step Protection Type                   | Overload: step circuit breaker<br>Short-circuit: step circuit breaker |
| Poles Description                      | 3P                                                                    |
| Capacitance Tolerance                  | - 5 % to 10 %                                                         |
| [Ui] Rated Insulation Voltage          | 690 V                                                                 |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV                                                                  |
| Maximum Permissible Voltage            | 1.1 x Un (8 hours over 24 hours) conforming to IEC 60831              |
| [Imp] Maximum Permanent<br>Current     | 1.3 x In at 400 V conforming to IEC 60831                             |
| Colour                                 | White (RAL 9003)                                                      |
| Location Of Connection                 | Top or bottom                                                         |
| Maximum Weight                         | 434 kg                                                                |
| Height                                 | 2200 mm                                                               |
| Width                                  | 800 mm                                                                |
| Depth                                  | 600 mm                                                                |

#### **Environment**

| Standards                                     | IEC 61439-2<br>IEC 61439-1<br>IEC 61921 |
|-----------------------------------------------|-----------------------------------------|
| Mounting Location                             | Indoor                                  |
| Ik Degree Of Protection                       | IK10                                    |
| Relative Humidity                             | 095 %                                   |
| Operating Altitude                            | <= 2000 m                               |
| Ambient Air Temperature For Operation         | -540 °C                                 |
| Average Ambient Air Temperature For Operation | 35 °C (over 24 hours)                   |

# **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 1.0 cm   |
| Package 1 Width              | 2.0 cm   |
| Package 1 Length             | 3.0 cm   |
| Package 1 Weight             | 434.0 kg |

## **Contractual warranty**

Warranty 18 months

Apr 25, 2024

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

**Eu Rohs Directive** 

Not applicable, out of EU RoHS legal scope