Specifications



fixed PowerLogic PFC Capacitor base, 50kvar 480V/60Hz

VLVB304

Main

Network Rated Voltage	480 V AC 60 Hz
Reactive Power Rating	50 kvar
Operating Mode	Fixed
Range Of Product	PowerLogic
Device Short Name	fixed capacitor bank

Complementary

Complementary	
Network Pollution Level	Low polluted
[Gh/Sn] Harmonic Pollution Rate	025 %
[Thdu] Total Harmonic Distorsion	05 %
Capacitor Technology	HDuty
Poles Description	3P
Capacitance Tolerance	- 5 % to 10 %
[Ui] Rated Insulation Voltage	690 V
[Uimp] Rated Impulse Withstand Voltage	2.5 kV
Maximum Permissible Voltage	1.1 x Un (8 hours over 24 hours) conforming to IEC 60831
[Imp] Maximum Permanent Current	1.8 x In at 480 V conforming to IEC 60831
Colour	White (RAL 9003)
Maximum Weight	64 kg
Height	700 mm
Width	600 mm
Depth	300 mm

Environment

Standards	IEC 61439-2 IEC 61921 IEC 61439-1
Mounting Location	Indoor
Ik Degree Of Protection	IK10
Relative Humidity	095 %
Operating Altitude	<= 2000 m
Ambient Air Temperature For Operation	-540 °C

Average Ambient Air Temperature 35 °C (over 24 hours) For Operation

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Weight	64 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope