Product data sheet

Specifications



cable for pulse/direction signal, Lexium SD3, 5V, shielded, 5m

VW3S8201R50

Main

Accessory / Separate Part Designation	Cable for pulse/direction signal
Accessory / Separate Part Type	Connecting cable
Accessory / Separate Part Category	Connection accessories
Accessory / Separate Part Destination	Between stepper drive SD326 and external impulsion generator
Range Compatibility	Lexium SD3
Type Of Cable	Shielded cable
Cable Length	5 m

Complementary

Product Compatibility	SD326
[Uc] Control Circuit Voltage	5 V
Electrical Connection	1 connector 24-pole Molex (SD326) Cable end open (external impulsion generator)

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	26.0 cm
Package 1 Length	28.0 cm
Package 1 Weight	464.0 g
Unit Type Of Package 2	S06
Number Of Units In Package 2	60
Package 2 Height	73.5 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	40.84 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Pvc Free	
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	
	China RoHS declaration