Product data sheet Characteristics

XUSLZD70320

protection tube - safety light curtain type 4 - acrylic - 324.8 mm - IP67



		2.
Range of product	Preventa Safety detection	
Accessory / separate part designation	IP67 protection tube	
Accessory / separate part type	Protection tube	
Accessory / separate part category	Protection accessories	
Product compatibility	XUSLDM0320 XUSLDS0320 XUSLB0320	
Accessory / separate part destination	Safety light curtain type 4	
Quantity per set	Set of 2	

Complementary

Complementary	
Height	324.8 mm
Material	Acrylic
Sensing distance reduction coefficient	0.90 Sn
Product weight	2.81 kg

Environment

IP degree of protection	IP67 conforming to IEC 60529	-
Resistance to chemical agents	Limited resistant against esters	. <u>u</u>
	Resistant alkalis	ב מ
	Limited resistant against chlorinated or aromatic hydrocarbons	Ę
	Resistant aqueous solutions	4
	Limited resistant against ketones	11. 11.
	Resistant aliphatic hydrocarbons	Ū
	Resistant to inorganic diluted acids	v o
	Resistant detergents and cleaners	7 0
Environmental characteristic	Humidity resistant	
	Resistant against immersion in water	;- 5
	UV resistant	.9
	Adverse weather resistant	i te
Ambient air temperature for operation	040 °C	ementation
Ambient air temperature for storage	-2570 °C	
		يِّ.

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0947 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
Contractual warranty	